



	Material: Caseal Butyl Rubber Sealant Strip Code: Various sizes Date of Issue: April 2022
1. Preparation and Company Identification:	Preparation trade name: BUTYL SEALANT Supplier: CASWICK LTD Address: Sandtoft Road, Belton, Nr Doncaster, DN9 1PN Telephone: (+44) 0142 787 2017 Emergency: As Above
<b>3. Hazard Identification:</b>	This product is not classified as dangerous for supply under the terms of the Chemicals (Hazard Information and Packaging for Supply) Regulations of 2002. The product is heated for some applications however and this leads to possibility of burns by contact between molten product and the skin. Also fumes from heated product could be harmful in areas of restricted ventilation.
2. Composition/Information on Ingredients:	No ingredients classified as hazardous
4. First Aid Measures:	For skin burns from hot product douse area in cold water. Seek medical advice. Otherwise: Skin Contact: Wash with soap and water Eye Contact: Wash with water Inhalation: Remove to fresh air. Seek medical attention if symptoms persist Ingestion: Seek medical advice (THIS SHEET IS TO BE SHOWN TO EMERGENCY/MEDICAL STAFF)
5. Firefighting Measures:	<b>Extinguishing Media:</b> Dry powder, CO₂ or foam <b>Do not use:</b> Water jet <b>Protective Equipment:</b> Self contained breathing apparatus may be needed in large files









6. Accidental Release Measures:	Personal Precautions: None		
	Environmental Precautions: Solid product. Presents no environmental problems if collected and disposed of correctly		
	•	. ,	
	Method of Cleaning: Collect	t in container. Dispose of as in Section 13	
7. Handling and Storage:	Handling: Heat resistant glo Gloves recommended for co	ves necessary when applying heated product. old applications	
	Storage: Store away from he	eat and open flame	
8. Exposure Control/			
Personal Protection:	Exposure Limits: Bitumen Fu	umes – 5mg/m3 8hr TWA	
	Oil Fumes – 5mg/m3 8hr TW	/A	
	Respiratory Protection: Ensu tape	re adequate ventilation when applying heated	
		ant gloves necessary when applying heated from skin wash with soap and water or use	
	Eye/Face Protection: As req product.	uired to avoid contact with hot bituminous	
9. Physical and Chemical Properties:	Appearance: Mastic Strip	Explosion Limits: Not applicable	
	Odour: Bituminous	Colour: Black	
	Specific Gravity:	<b>Softening Point:</b> 105°C approx. (standard) 125°C approx (tropical)	
	% Volatile: Nil	Solubility in Water: Nil	
	Flash Point: Not applicable	Boiling Point: Not applicable	
10. Stability and Reactivity:	Conditions to Avoid: In store	e, heat and open flame	
	Materials to Avoid: Not appl	icable	
	Hazardous Decomposition F oxides of carbon	Products: In a fire, black smoke,	
11. Toxicological Information:	Prolonged and repeated cor	ntact with skin may cause irritation	
12. Ecological Information:	None available		









14. Transport Information:	Special Precautions in Carriage:	None
	Main Risk:	None
	Subsidiary Risk:	None
	Classification Date: 23/10/02	
	UN NO.	None
	Packing Group:	None
	Other:	None

## **16. Other Information:**

## Uses: Butyl Sealant

This data contained in this Data Safety Sheet has been supplied as required by the **Chemical (Hazard Identification and Packaging) Regulations 2009**, as amended, for the purpose of protecting the health and safety of industrial and commercial users who are deemed capable of understanding and acting on the information provided.

## Please ensure that it is passed to the appropriate person(s) in your company, who are capable of acting on the information.

This information is given in good faith, being based on the latest knowledge available to Caswick Ltd. No known relevant information has been omitted from the Material Safety Data Sheet and the information provided is designed to enable the user to use the product safely.

The user should not assume on the basis of the information provided in this sheet that the product is suitable for any abnormal use.

If the information provided is insufficient to ensure safety in any particular application, contact Caswick Ltd for further advice before the proposed application is undertaken.



